

# MATERIAL SAFETY DATA SHEET

Prepared to U.S. OSHA, CMA, ANSI, Canadian WHMIS, Australian NOHSC, New Zealand, Japanese, and European Union Standards

## 1. PRODUCT IDENTIFICATION

**TRADE/MATERIAL NAME:** 3D DENSIFIER  
**CHEMICAL NAMES:** Proprietary Silicate Mixture  
**PRODUCT USE:** Concrete Sealant  
**SYNONYMS:** Not Applicable  
**U.N. NUMBER:** Not Applicable  
**U.N. DANGEROUS GOODS CLASS/SUBSIDIARY RISK:** Not Applicable  
**HAZCHEM CODE (Australia):** Not Applicable  
**POISONS SCHEDULE NUMBER (Australia):** Not Applicable  
**SUPPLIER/MANUFACTURER'S NAME (USA/Canada):** Ameripolish  
**Address:** 120 Commercial Ave  
Lowell, AR 72745  
**Emergency Phone:** 1-800-255-3924 (CHEM-TEL) in U.S., Canada, Puerto Rico,  
U.S. Virgin Islands  
+1-813-248-0585 (outside areas above, call collect)  
(847) 793-6945  
**Business Phone:**  
**SUPPLIER/IMPORTER'S NAME (Europe):**  
**Address:**  
**Emergency Phone:**  
**Business Phone:**  
**SUPPLIER/IMPORTER'S NAME (Australia):**  
**Address:**  
**Emergency Phone:**  
**Business Phone:**  
**SUPPLIER/IMPORTER'S NAME (New Zealand):**  
**Address:**  
**Emergency Phone:**  
**Business Phone:**

NOTE: ALL United States Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalent Standards, Canadian WHMIS [Controlled Products Regulations], European Union [Regulation (EC) 1907/2006 Annex II], Australian [NOHSC:2011 (2003)], and Japanese Industrial Standard (JIS Z 7250: 2005) required information is included in appropriate sections based on the U.S. ANSI Z400.1-2004 format. This product has been classified in accordance with the hazard criteria of the countries listed above.

## 2. HAZARD IDENTIFICATION

**EU/AUSTRALIAN LABELING AND CLASSIFICATION:** This product does meet the definition of Irritant as defined by European Union Council Directive 67/548/EEC and subsequent Directives and by the Australian National Occupational Health and Safety Commission [NOHSC(1008:2004)].

Classification: Xi: Irritant.

Risk Phrases: R 43; R 52/53

**EMERGENCY OVERVIEW: Product Description:** This product is a mildly basic, odorless, milky liquid. **Health Hazards:** This product may mildly to moderately irritate the eyes, skin, respiratory tract, and gastrointestinal system. **Flammability Hazards:** If involved in a fire, this product will release smoke, acrid vapors and toxic gases (e.g., carbon oxides and lithium compounds). If the water in this product evaporates off, the remaining residue may be combustible. **Reactivity Hazards:** This product is not reactive. **Environmental Hazards:** Large quantities released to the environment may have an adverse effect. **Emergency Considerations:** Emergency responders should wear appropriate protection for the situation to which they respond.

## 3. COMPOSITION and INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS #	EINECS #	AICS Inventory Listing	% w/w	EU CLASSIFICATION FOR COMPONENTS
Proprietary Surfactant				1-5	Hazard Classification: Not Applicable Risk Phrases: Not Applicable
Proprietary Piperidyl Sebacate Derivatives			Listed	1-5	Hazard Classification: Irritant, Dangerous for the Environment Risk Phrases: R 43, R 50/53

See Section 16 for full text of Ingredient Risk Phrases

### 3. COMPOSITION and INFORMATION ON INGREDIENTS (Continued)

CHEMICAL NAME	CAS #	EINECS #	AICS Inventory Listing	% w/w	EU CLASSIFICATION FOR COMPONENTS
Proprietary UV-absorbing monomer and or Polymer			Listed	1-5	Hazard Classification: Irritant, Dangerous for the Environment Risk Phrases: R 43, R 51/53
Proprietary Surfactant				1-5	Hazard Classification: Not Applicable Risk Phrases: Not Applicable
Proprietary Silane			Listed	1-5	Hazard Classification: Not Applicable Risk Phrases: Not Applicable
Proprietary Siloxanes and Silicones			Listed	1-5	Hazard Classification: Not Applicable Risk Phrases: Not Applicable
Proprietary Hydroxide			Listed	10-30	Hazard Classification: Corrosive, Harmful. Risk Phrases: R 20/22, R 35
Water and other components. Each of the other components is present in less than 1 percent concentration (0.1% concentration for potential carcinogens, reproductive toxins, respiratory tract sensitizers, and mutagens).				Balance	Hazard Classification: Not Applicable Risk Phrases: Not Applicable

See Section 16 for full text of Ingredient Risk Phrases

### 4. FIRST-AID MEASURES

If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Take a copy of label and MSDS to physician or health professional with the contaminated individual.

**SKIN EXPOSURE:** If adverse skin effects occur, discontinue use and flush contaminated area. Seek medical attention if adverse effect occurs after flushing.

**EYE EXPOSURE:** If this product contaminates the eyes, rinse eyes under gently running water. Use sufficient force to open eyelids and then "roll" eyes while flushing. Minimum flushing is for 20 minutes. The contaminated individual must seek medical attention if any adverse effect continues after rinsing.

**INHALATION:** If vapors of this product are inhaled, remove victim to fresh air. If necessary, use artificial respiration to support vital functions. Seek medical attention if adverse effect continues after removal to fresh air.

**INGESTION:** If this product is swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. If professional advice is not available, DO NOT INDUCE VOMITING. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or unable to swallow. If victim is convulsing, maintain an open airway and obtain immediate medical attention.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Pre-existing dermatitis and other skin disorders may be aggravated by overexposures to this product.

**RECOMMENDATIONS TO PHYSICIANS:** Treat symptoms and eliminate exposure.

### 5. FIRE-FIGHTING MEASURES

**FLASH POINT:** Not flammable.

**AUTOIGNITION TEMPERATURE:** Not applicable.

**FLAMMABLE LIMITS (in air by volume, %):** Not applicable.

**FIRE EXTINGUISHING MATERIALS:** Use extinguishing materials suitable for the surrounding area.

Water Spray: OK      Carbon Dioxide: OK      Foam: OK  
Dry Chemical: OK      Halon: OK      Other: OK

**FIRE EXTINGUISHING MATERIALS NOT TO BE USED:** None known.


**UNUSUAL FIRE AND EXPLOSION HAZARDS:** When involved in a fire, this material will ignite and produce irritating vapors and toxic gases (e.g., carbon oxides and lithium compounds). If the water in this product evaporates off, the remaining residue may be combustible.

Explosion Sensitivity to Mechanical Impact: Not sensitive.

Explosion Sensitivity to Static Discharge: Not sensitive.

**SPECIAL FIRE-FIGHTING PROCEDURES:** Incipient fire responders should wear eye protection. Structural firefighters must wear Self-

Contained Breathing Apparatus (SCBA) and full protective equipment. Chemical resistant clothing may be necessary. Move containers from fire area if it can be done without risk to personnel. Water spray can be used to cool fire-exposed containers. Water fog or spray can also be used by trained firefighters to disperse this product's vapors and to protect personnel. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.



Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate  
3 = Serious 4 = Severe

### 6. ACCIDENTAL RELEASE MEASURES

**SPILL AND LEAK RESPONSE:** Proper protective equipment should be used. In the event of a spill, clear the area and protect people. Spills will be slippery. The atmosphere must have levels of components lower than those listed in Section 8, (Exposure Controls and Personal Protective Equipment) if applicable, and have at least 19.5 percent oxygen before personnel can be allowed into the area without Self-Contained Breathing Apparatus (SCBA).

## 6. ACCIDENTAL RELEASE MEASURES (Continued)

### SPILL AND LEAK RESPONSE (continued):

Small Spills: Wear rubber gloves, splash goggles, and appropriate body protection. Wipe up spilled liquid with polypads or other suitable absorbent materials. Wash contaminated area with soap and water, absorb with paper towels, and rinse with water.

Large Spills: Trained personnel following pre-planned procedures should handle non-incident releases. Minimum Personal Protective Equipment should be rubber gloves, rubber boots, face shield, and Tyvek suit. Minimum level of personal protective equipment for releases in which the level of oxygen is less than 19.5% or is unknown must be **Level B: triple-gloves (rubber gloves and nitrile gloves over latex gloves), chemical resistant suit and boots, hard hat, and Self-Contained Breathing Apparatus**. Wipe up spilled liquid with polypads or other suitable absorbent materials. Prevent material from entering sewer or confined spaces, waterways, soil or public waters. Monitor area and confirm levels are below exposure limits given in Section 8 (Exposure Controls-Personal Protection), if applicable, before non-response personnel are allowed into the spill area.

Decontaminate the area thoroughly. Place all spill residue in an appropriate container and seal. If necessary, discard all contaminated response equipment or rinse with soapy water before returning such equipment to service. Do not mix with wastes from other materials. Dispose of in accordance with applicable Federal, State, and local procedures (see Section 13, Disposal Considerations).

## 7. HANDLING and USE

**WORK PRACTICES AND HYGIENE PRACTICES:** As with all chemicals, avoid getting this material ON YOU or IN YOU. Do not eat, drink, smoke, or apply cosmetics while handling this product. Wash hands thoroughly after handling this product or containers of this product. Avoid breathing vapors or mists generated by this product. Use

in a well-ventilated location. Follow SPECIFIC USE INSTRUCTIONS supplied with product.

**STORAGE AND HANDLING PRACTICES:** Employees must be trained to properly use this product. Use in a well ventilated location. Open containers slowly on a stable surface. Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Store away from incompatible materials (see Section 10, Stability and Reactivity). Material should be stored in secondary containers, as appropriate. Post warning and "NO SMOKING" signs in storage and use areas, as appropriate. Keep container tightly closed when not in use. Inspect all incoming containers before storage to ensure containers are properly labeled and not damaged.

Empty containers may contain residual liquid or vapors; therefore, empty packages should be handled with care.

**SPECIFIC USE(S):** This product is for use as a concrete coating. Follow all industry standards for use of this product.

**PROTECTIVE PRACTICES DURING MAINTENANCE OF CONTAMINATED EQUIPMENT:** Follow practices indicated in Section 6 (Accidental Release Measures). Make certain that application equipment is locked and tagged-out safely, if necessary. Collect all rinsates and dispose of according to applicable U.S. Federal, State, and local procedures or with procedures of the EU and its member states, Australia, New Zealand, Japan, or Canada and its Provinces.

## 8. EXPOSURE CONTROLS - PERSONAL PROTECTION

**VENTILATION AND ENGINEERING CONTROLS:** Use with adequate ventilation to ensure exposure levels are maintained below the limits provided below. Exhaust directly to the outside, taking necessary precautions for environmental protection. If necessary, refer to Australian National Code of Practice for the Control of Workplace Hazardous Substances [NOHSC: 2007 (1994)] for further information.

**EXPOSURE LIMITS/GUIDELINES:**

CHEMICAL NAME	CAS #	EXPOSURE LIMITS IN AIR							
		ACGIH-TLV		OSHA-PEL		NIOSH-RELs		NIOSH	OTHER
		TWA mg/m <sup>3</sup>	STEL mg/m <sup>3</sup>	TWA mg/m <sup>3</sup>	STEL mg/m <sup>3</sup>	TWA mg/m <sup>3</sup>	STEL mg/m <sup>3</sup>	IDLH mg/m <sup>3</sup>	mg/m <sup>3</sup>
Proprietary Surfactant		NE	NE	NE	NE	NE	NE	NE	NE
Proprietary Hydroxide		0.025	NE	0.025	NE	0.025	NE	NE	AIHA WEEL: STEL = 1 ceiling
Proprietary Piperidyl Sebacate Derivative		NE	NE	NE	NE	NE	NE	NE	NE
Proprietary UV- absorbing monomer and or Polymer		NE	NE	NE	NE	NE	NE	NE	NE
Proprietary Surfactant		NE	NE	NE	NE	NE	NE	NE	NE
Proprietary Silane		NE	NE	NE	NE	NE	NE	NE	NE
Proprietary Siloxanes and Silicones		NE	NE	NE	NE	NE	NE	NE	NE

NE = Not Established. See Section 16 for Definitions of Other Terms Used

**INTERNATIONAL OCCUPATIONAL EXPOSURE LIMITS:** Currently, there are additional exposure limit values established by various countries for some components of this mixture. More current limits may be available; individual countries should be consulted to determine if newer limits are available.

**PROPRIETARY ALKALI HYDROXIDE:**

Japan: OEL = Japan: OEL = 1 mg/m<sup>3</sup>, JAN 1999

**PROPRIETARY ALKALI HYDROXIDE (continued):**

United Kingdom: STEL = 1 mg/m<sup>3</sup>, SEP 2000

## 8. EXPOSURE CONTROLS - PERSONAL PROTECTION (Continued)

The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132), equivalent standards of Canada (including CSA Standard Z94.4-02 and CSA Standard Z94.3-07), standards of EU member states (including EN 529:2005 for respiratory PPE, CEN/TR 15419:2006 for hand/body protection, and CR 13464:1999 for face/eye protection), standards of Australia (including AS/NZS 1715:1994 for respiratory PPE, AS/NZS 4501.2:2006 for protective clothing, AS/NZS 2161.1:2000 for glove selection, and AS/NZS 1336:1997 for eye protection), or standards of Japan (including JIS T 8116:2005 for glove selection, JIS T 8150:2006 for respiratory PPE, JIS T 8147:2003 for eye protectors, and JIS T 8030:2005 for protective clothing). Please reference applicable regulations and standards for relevant details.

**RESPIRATORY PROTECTION:** If mists, sprays or vapors from this product are created during use, use appropriate respiratory protection. If necessary, use only respiratory protection authorized in the U.S. Federal OSHA Respiratory Protection Standard (29 CFR 1910.134), equivalent U.S. State standards, Canadian CSA Standard Z94.4-02, European Standard EN 529:2005, EU member state standards, Australian Standard 1716-Respiratory Protective Devices and Australian Standard 1715-Selection, Use, and Maintenance of Respiratory Protective Devices, or Japanese Standard JIS T 8150:2006. Oxygen levels below 19.5% are considered IDLH by OSHA. In such atmospheres, use of a full-facepiece pressure/demand SCBA or a full facepiece, supplied air respirator with auxiliary self-contained air supply is required under U.S. Federal OSHA's Respiratory Protection Standard (1910.134-1998).

**EYE PROTECTION:** Splash goggles or safety glasses. If necessary, refer to U.S. OSHA 29 CFR 1910.133, Canadian CSA Standard Z94.3-07, European Standard CR 13464:1999, Australian Standard 1337-Eye Protection for Industrial Applications and Australian Standard 1336-Recommended Practices for Eye Protection in the Industrial Environment, or Japanese Standard JIS T 8147:2003.

**HAND PROTECTION:** Wear latex or rubber gloves for routine industrial use. Use triple gloves for spill response. If necessary, refer to U.S. OSHA 29 CFR 1910.138, Australian Standard 2161-Industrial Safety Gloves and Mittens, European Standard CEN/TR 15419:2006, or Japanese Standard JIS T 8116:2005.

**BODY PROTECTION:** Use body protection appropriate for task (e.g., lab coat, coveralls, Tyvek suit). If necessary, refer to OSHA Technical Manual (Section VII: Personal Protective Equipment), European Standard CEN/TR 15419:2006, Australian Standard 3765-Clothing for Protection Against Hazardous Chemicals, or Japanese Standard JIS T 8030:2005. If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects may pierce the soles of the feet or where employee's feet may be exposed to electrical hazards, use foot protection, as described in U.S. OSHA 29 CFR 1910.136, Canadian CSA Standard Z195.1-02, *Guideline on Selection, Care, and Use of Protective Footwear*, or European Standard CEN ISO/TR 18690:2006.

---

## 9. PHYSICAL and CHEMICAL PROPERTIES

**BOILING POINT:** Not established.

**EVAPORATION RATE (*n*-BuAc = 1):** Not established.

**VAPOR PRESSURE @ 25°C:** Not established.

**ODOR THRESHOLD:** Not established.

**COEFFICIENT WATER/OIL DISTRIBUTION:** Not established.

**APPEARANCE, ODOR, AND COLOR:** This product a mildly basic, odorless, milky liquid.

**HOW TO DETECT THIS SUBSTANCE (warning properties in event of accidental release):** The appearance may be characteristics to distinguish a release of this product.

**FREEZING/MELTING POINT:** Not established.

**SOLUBILITY IN WATER:** Soluble.

**SPECIFIC GRAVITY (water = 1):** Not established.

**pH:** 10.9

**VAPOR DENSITY (air = 1):** Not established.

---

## 10. STABILITY and REACTIVITY

**STABILITY:** This product is stable when properly stored at normal temperature and pressures (see Section 7, Handling and Storage).

**DECOMPOSITION PRODUCTS:** Combustion: If exposed to extremely high temperatures, thermal decomposition may generate irritating fumes and toxic gases (e.g., carbon oxides and lithium compounds). Hydrolysis: None known.

**MATERIALS WITH WHICH SUBSTANCE IS INCOMPATIBLE:** This product is incompatible with strong oxidizers.

**HAZARDOUS POLYMERIZATION:** Will not occur.

**CONDITIONS TO AVOID:** Avoid exposure to or contact with extreme temperatures and incompatible chemicals.

---

## 11. TOXICOLOGICAL INFORMATION

**SYMPTOMS OF OVEREXPOSURE BY ROUTE OF EXPOSURE:** The health hazard information provided below is pertinent to employees using this product in an occupational setting. The following paragraphs describe the symptoms of exposure by route of exposure.

**INHALATION:** Inhalation overexposures to vapors, mists, and sprays of this product can mildly to moderately irritate the nose, throat, and lungs and cause coughing.

# 11. TOXICOLOGICAL INFORMATION (Continued)

**CONTACT WITH SKIN or EYES:** Direct eye contact can cause irritation, redness, and tearing. Skin contact can be mildly to moderately irritating. Prolonged or repeated skin overexposures may cause dermatitis (dry red skin).

**SKIN ABSORPTION:** The components of this product are not known to be absorbed through intact skin.

**INGESTION:** Ingestion is not a significant route of occupational overexposure and is unlikely to occur. If this product is swallowed, it can irritate the mouth, throat, esophagus and other tissues of the digestive system. Symptoms of ingestion may include nausea, vomiting, and diarrhea.

**INJECTION:** Accidental injection of this product, via laceration or puncture by a contaminated object can cause redness at the site of injection.

**HEALTH EFFECTS OR RISKS FROM EXPOSURE:** An **Explanation in Lay Terms.** Overexposure to this product may cause the following health effects:

Acute: Overexposures to this product can mildly to moderately irritate the eyes, skin, gastrointestinal tract, and respiratory tract.

Chronic: Prolonged or repeated skin overexposures may cause dermatitis (dry red skin).

**TARGET ORGANS:** Acute: Skin, eyes, respiratory system. Chronic: Skin.

**TOXICITY DATA:** The following toxicological data are available for components of this product present in greater than 1% concentration.

**PROPRIETARY ALKALI HYDROXIDE:**

LD<sub>50</sub> (oral, rat) = 210 mg/kg; Behavioral: somnolence (general depressed activity), convulsions or effect on seizure threshold; Nutritional and Gross Metabolic: weight loss or decreased weight gain  
 LC<sub>50</sub> (inhalation, rat) = 960 mg/m<sup>3</sup>/4 hours; Lungs, Thorax, or Respiration: other changes  
 LD<sub>50</sub> (intratracheal, rat) = 8200 g/kg; Lungs, Thorax, or Respiration: other changes; Blood: hemorrhage  
 LD<sub>50</sub> (oral, mouse) = 363 mg/kg; Behavioral: somnolence (general depressed activity), convulsions or effect on seizure threshold; Nutritional and Gross Metabolic: weight loss or decreased weight gain  
 LDLo (subcutaneous, mouse) = 300 mg/kg  
 TDLo (oral, mammal) = 9100 g/kg/26 weeks/intermittent; Liver: liver function tests impaired; Blood: pigmented or nucleated red blood cells; Nutritional and Gross Metabolic: weight loss or decreased weight gain  
 TCLo (inhalation, mammal) = 8 mg/m<sup>3</sup>/4 hours/30 days/intermittent; Lungs, Thorax, or Respiration: other changes

**PROPRIETARY HYDROXYPHENYL**

**BENZOTRIAZOLE DERIVATIVE (continued):**  
 Standard Draize Test (skin, human) = 500 mg/48 hours  
 LD<sub>50</sub> (oral, rat) = 27,500 mg/kg; Kidney, Ureter, Bladder: other changes  
 LD<sub>50</sub> (oral, rat) = 32 g/kg  
 LD<sub>50</sub> (oral, rat) = 22 g/kg  
 LD<sub>50</sub> (oral, rat) = 30,200 mg/kg  
 LD<sub>50</sub> (oral, rat) = 44,200 mg/kg; Kidney, Ureter, Bladder: other changes  
 LD<sub>50</sub> (oral, rat) = 600 mg/kg  
 LD<sub>50</sub> (oral, rat) = 30 g/kg  
 LD<sub>50</sub> (oral, rat) = 31,600 mg/kg  
 LD<sub>50</sub> (oral, rat) = 31,640 mg/kg; Kidney, Ureter, Bladder: other changes  
 LD<sub>50</sub> (oral, rat) = 51,200 mg/kg; Kidney, Ureter, Bladder: other changes  
 LD<sub>50</sub> (oral, rat) = 50 gm/kg  
 LD<sub>50</sub> (oral, rat) = 1054 mg/kg  
 LD<sub>50</sub> (oral, rat) = 45 g/kg  
 LD<sub>50</sub> (oral, rat) = 51,310 mg/kg; Kidney, Ureter, Bladder: other changes  
 LD<sub>50</sub> (oral, rat) > 4 g/kg  
 LD<sub>50</sub> (intraperitoneal, rat) = 9 g/kg; Kidney, Ureter, Bladder: other changes  
 LD<sub>50</sub> (intraperitoneal, rat) = 9708 mg/kg

**PROPRIETARY HYDROXYPHENYL**

**BENZOTRIAZOLE DERIVATIVE (continued):**  
 LD<sub>50</sub> (intraperitoneal, rat) = 16 g/kg; Kidney, Ureter, Bladder: other changes  
 LD<sub>50</sub> (intraperitoneal, rat) = 17 g/kg  
 LD<sub>50</sub> (intraperitoneal, rat) = 6790 mg/kg; Kidney, Ureter, Bladder: other changes  
 LD<sub>50</sub> (intraperitoneal, rat) = 15,390 mg/kg; Kidney, Ureter, Bladder: other changes  
 LD<sub>50</sub> (intraperitoneal, rat) = 473 mg/kg  
 LD<sub>50</sub> (intraperitoneal, rat) = 14,100 mg/kg  
 LD<sub>50</sub> (intraperitoneal, rat) = 15,570 mg/kg; Kidney, Ureter, Bladder: other changes  
 LD<sub>50</sub> (intraperitoneal, rat) = 12,600 mg/kg; Kidney, Ureter, Bladder: other changes  
 LD<sub>50</sub> (subcutaneous, rat) = 16 g/kg; Kidney, Ureter, Bladder: other changes  
 LD<sub>50</sub> (intravenous, rat) = 7500 mg/kg  
 LD<sub>50</sub> (intravenous, rat) = 8550 mg/kg  
 LD<sub>50</sub> (intravenous, rat) = 8 g/kg; Blood: change in clotting factors  
 LD<sub>50</sub> (intravenous, rat) = 7130 mg/kg  
 LD<sub>50</sub> (intravenous, rat) = 13 g/kg; Kidney, Ureter, Bladder: other changes  
 LD<sub>50</sub> (intravenous, rat) = 7900 g/kg  
 LD<sub>50</sub> (oral, mouse) = 31 g/kg  
 LD<sub>50</sub> (oral, mouse) = 28,915 mg/kg  
 LD<sub>50</sub> (oral, mouse) = 36 g/kg  
 LD<sub>50</sub> (intraperitoneal, mouse) = 2 g/kg; Lungs, Thorax, or Respiration: respiratory depression  
 LD<sub>50</sub> (intraperitoneal, mouse) = 8 g/kg; Lungs, Thorax, or Respiration: respiratory depression  
 LD<sub>50</sub> (intraperitoneal, mouse) = 9700 mg/kg  
 LD<sub>50</sub> (intravenous, mouse) = 16 g/kg; Kidney, Ureter, Bladder: other changes  
 LD<sub>50</sub> (subcutaneous, mouse) = 18 g/kg; Kidney, Ureter, Bladder: other changes  
 LD<sub>50</sub> (oral, rabbit) = 17,300 mg/kg; Kidney, Ureter, Bladder: other changes  
 LD<sub>50</sub> (oral, rabbit) = 26,800 mg/kg; Kidney, Ureter, Bladder: other changes  
 LD<sub>50</sub> (oral, rabbit) = 76 g/kg  
 LD<sub>50</sub> (oral, rabbit) = 28,900 mg/kg; Kidney, Ureter, Bladder: other changes  
 LD<sub>50</sub> (oral, rabbit) = 17,300 mg/kg  
 LD<sub>50</sub> (oral, rabbit) = 76 g/kg; Kidney, Ureter, Bladder: other changes  
 LD<sub>50</sub> (oral, rabbit) = 19 g/kg  
 LD<sub>50</sub> (skin, rabbit) > 20 mL/kg  
 LD<sub>50</sub> (skin, rabbit) > 20 g/kg

**HAZARDOUS MATERIAL IDENTIFICATION SYSTEM**

<b>HEALTH HAZARD</b>	(BLUE)	1
----------------------	--------	---

<b>FLAMMABILITY HAZARD</b>	(RED)	0
----------------------------	-------	---

<b>PHYSICAL HAZARD</b>	(YELLOW)	0
------------------------	----------	---

**PROTECTIVE EQUIPMENT**

EYES	RESPIRATORY	HANDS	BODY
	SEE SECTION 8		SEE SECTION 8

For Routine Industrial Use and Handling Applications

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate  
 3 = Serious 4 = Severe \* = Chronic hazard

**PROPRIETARY HYDROXYPHENYL**

**BENZOTRIAZOLE DERIVATIVE (continued):**  
 LD<sub>50</sub> (skin, rabbit) > 20 gm/kg  
 LD<sub>50</sub> (oral, guinea pig) = 15,700 mg/kg; Kidney, Ureter, Bladder: other changes  
 LD<sub>50</sub> (oral, guinea pig) = 19,600 mg/kg; Kidney, Ureter, Bladder: other changes  
 LD<sub>50</sub> (oral, guinea pig) = 28,900 mg/kg; Kidney, Ureter, Bladder: other changes  
 LD<sub>50</sub> (oral, guinea pig) = 28 g/kg  
 LD<sub>50</sub> (oral, guinea pig) = 22,500 mg/kg  
 LD<sub>50</sub> (oral, guinea pig) = 50,900 mg/kg; Kidney, Ureter, Bladder: other changes  
 LD<sub>50</sub> (intravenous, dog) 3 g/kg  
 LD (oral, rat) > 4 g/kg  
 LD (oral, rabbit) > 1 g/kg  
 LDLo (intravenous, rat) = 22 g/kg; Cardiac: arrhythmias (including changes in conduction); Vascular: BP lowering not characterized in autonomic section; Kidney, Ureter, Bladder: hematuria  
 LDLo (intravenous, rat) = 3 mg/kg  
 TDLo (oral, rat) = 1845 mg/kg/90 days/continuous; Liver: other changes; Kidney, Ureter, Bladder: changes primarily in glomeruli; Nutritional and Gross Metabolic: weight loss or decreased weight gain  
 TDLo (oral, rat) = 1476 mg/kg/90 days/continuous; Nutritional and Gross Metabolic - weight loss or decreased weight gain; Related to Chronic Data: death  
 TCLo (inhalation, rat) = 567 mg/m<sup>3</sup>/6 hours/2 weeks/intermittent; Lungs, Thorax, or Respiration: changes in lung weight; Nutritional and Gross Metabolic: weight loss or decreased weight gain  
 TDLo (intravaginal, mouse) = 416 mg/kg; years-intermittent: Tumorigenic: equivocal tumorigenic agent by RTECS criteria; Reproductive: Tumorigenic effects: other reproductive system tumors  
 Standard Draize Test (skin, rabbit) = 500 mg/24 hours; Mild  
 Standard Draize Test (eye, rabbit) = 500 mg/24 hours; Mild  
 Standard Draize Test (eye, rabbit) = 100 L; Mild  
 DNA Damage (microorganism) = 100 g/L  
 Cytogenetic Analysis (hamster cells) = 50 pph  
**PROPRIETARY SILOXANES AND SILICONES:**  
 Open Irritation Test (Skin-Rabbit) 500 mg: Mild

## 11. TOXICOLOGICAL INFORMATION (Continued)

### TOXICITY DATA (continued):

PROPRIETARY SILOXANES AND SILICONES (continued):	PROPRIETARY SILOXANES AND SILICONES (continued):	PROPRIETARY SILOXANES AND SILICONES (continued):
Standard Draize Test Eye-Rabbit 100 mg: Mild	TCLo (Inhalation-Rat) 119 mg/m <sup>3</sup> /6 hours/4 weeks- intermittent: Nutritional and Gross Metabolic: weight loss or decreased weight gain	TDLo (Oral-Rat) 30 gm/kg: female 6-15 day(s) after conception: Reproductive: Maternal Effect: other effects; Specific Developmental Abnormalities: musculoskeletal system
LD <sub>50</sub> (Oral-Rat) 22,600 µL/kg		
LD <sub>50</sub> (Skin-Rabbit) 3970 µL/kg		
LCLo (Inhalation-Rat) 5300 mg/m <sup>3</sup> /4 hours: Sense Organs and Special Senses (Eye): lachrymation; Nutritional and Gross Metabolic: weight loss or decreased weight gain	TCLo (Inhalation-Rat) 734 mg/m <sup>3</sup> /6 hours/9 days- intermittent: Nutritional and Gross Metabolic: weight loss or decreased weight gain; Biochemical: Enzyme inhibition, induction, or change in blood or tissue levels: transaminases; Related to Chronic Data: death	Mutation in Microorganisms (Bacteria-Salmonella typhimurium) 100 µg/plate

**IRRITANCY OF PRODUCT:** The liquid and vapors of this product can mildly to moderately irritate contaminated tissue.

**SENSITIZATION OF PRODUCT:** This product is not currently known to cause allergic skin or respiratory reaction.

**CARCINOGENIC POTENTIAL OF COMPONENTS:** It cannot be confirmed that the proprietary components of this product are not found on the following lists: U.S. EPA, U.S. NTP, U.S. OSHA, U.S. NIOSH, GERMAN MAK, IARC, or ACGIH and therefore are neither considered to be nor suspected to be cancer-causing agents by these agencies.

**REPRODUCTIVE TOXICITY INFORMATION:** Listed below is information concerning the effects components of this product and its components on human and animal reproductive systems.

**Mutagenicity:** The components of this product are not reported to cause human mutagenic effects.

**Embryotoxicity:** The components of this product are not reported to cause human embryotoxic effects.

**Teratogenicity:** The components of this product are not reported to cause teratogenic effects in humans.

**Reproductive Toxicity:** The components of this product are not reported to cause human reproductive effects.

*A **mutagen** is a chemical that causes permanent changes to genetic material (DNA) such that the changes will propagate through generation lines. An **embryo toxin** is a chemical that causes damage to a developing embryo (i.e. within the first eight weeks of pregnancy in humans), but the damage does not propagate across generational lines. A **teratogen** is a chemical that causes damage to a developing fetus, but the damage does not propagate across generational lines. A **reproductive toxin** is any substance that interferes in any way with the reproductive process.*

**ACGIH BIOLOGICAL EXPOSURE INDICES (BEIs):** Currently, there are no ACGIH Biological Exposure Indices (BEIs) determined for components of this product.

---

## 12. ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

**MOBILITY:** This product has not been tested for mobility in soil.

**PERSISTENCE AND BIODEGRADABILITY:** This product has not been tested for persistence or biodegradability. It is expected that the components of this product will slowly degrade in the environment and form a variety of organic and inorganic materials; however, no specific information is known. Additional information is available for components of this product as follows:

**PROPRIETARY HYDROXYPHENYL BENZOTRIAZOLE DERIVATIVE:**

Solubility: Readily soluble in water.

Degradation: This compound is chemically identical to the natural amino acid L-Serine and can therefore be degraded microbiologically.

**BIO-ACCUMULATION POTENTIAL:** This product has not been tested for bio-accumulation potential.

**ECOTOXICITY:** Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. All releases to terrestrial, atmospheric and aquatic environments should be avoided. Additional aquatic toxicity information is available for components of this product as follows:

**PROPRIETARY HYDROXYPHENYL BENZOTRIAZOLE DERIVATIVE:**

Toxic to fishes

**OTHER ADVERSE EFFECTS:** This product does not contain any component with known ozone depletion potential.

**ENVIRONMENTAL EXPOSURE CONTROLS:** Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways.

---

## 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHODS:** It is the responsibility of the generator to determine at the time of disposal whether the product meets the criteria of a hazardous waste per regulations of the area in which the waste is generated and/or disposed of. Waste disposal must be in accordance with appropriate Federal, State, and local regulations. This product, if unaltered by use, may be disposed of by treatment at a permitted facility or as advised by your local hazardous waste regulatory authority. Shipment of wastes must be done with appropriately permitted and registered transporters.

**DISPOSAL CONTAINERS:** Waste materials must be placed in and shipped in appropriate 5-gallon or 55-gallon poly or metal waste pails or drums. Permeable cardboard containers are not appropriate and should not be used.

Ensure that any required marking or labeling of the containers be done to all applicable regulations.

**PRECAUTIONS TO BE FOLLOWED DURING WASTE HANDLING:** Wear proper protective equipment when handling waste materials.

**U.S. EPA WASTE NUMBER:** Not applicable.

### 13. DISPOSAL CONSIDERATIONS (Continued)

EWC WASTE CODE: 08 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS: 08 04 99: Wastes from MFSU of adhesives and sealants (including waterproofing products); wastes not otherwise specified.

---

### 14. TRANSPORTATION INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION REGULATIONS: This product is not classified as dangerous goods, per U.S. DOT regulations, under 49 CFR 172.101.

TRANSPORT CANADA TRANSPORTATION OF DANGEROUS GOODS REGULATIONS: This product is not classified as Dangerous Goods, per regulations of Transport Canada.

INTERNATIONAL AIR TRANSPORT ASSOCIATION (IATA): This product is not classified as dangerous goods under rules of IATA.

INTERNATIONAL MARITIME ORGANIZATION (IMO) DESIGNATION: This product is not classified as Dangerous Goods by the International Maritime Organization.

EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY ROAD (ADR): This product is not classified by the United Nations Economic Commission for Europe to be dangerous goods.

AUSTRALIAN FEDERAL OFFICE OF ROAD SAFETY CODE FOR THE TRANSPORTATION OF DANGEROUS GOODS BY ROAD OR RAIL: This product is not classified as dangerous goods, per regulations of the Federal Office of Road Safety.

---

### 15. REGULATORY INFORMATION

#### **UNITED STATES REGULATIONS:**

U.S. SARA REPORTING REQUIREMENTS: It cannot be confirmed that the proprietary components of this product are not subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act.

U.S. SARA HAZARD CATEGORIES (SECTION 311/312, 40 CFR 370-21): ACUTE: No; CHRONIC: No; FIRE: No; REACTIVE: No; SUDDEN RELEASE: No

U.S. SARA THRESHOLD PLANNING QUANTITY: There are no specific Threshold Planning Quantities for this product. The default Federal MSDS submission and inventory requirement filing threshold of 10,000 lb (4,540 kg) may apply, per 40 CFR 370.20.

U.S. CERCLA REPORTABLE QUANTITY (RQ): Not applicable.

U.S. TSCA INVENTORY STATUS: It cannot be confirmed that the proprietary components of this product are listed on the TSCA Inventory.

OTHER U.S. FEDERAL REGULATIONS: Not applicable.

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROPOSITION 65): It cannot be confirmed that the proprietary components of this product are not on the California Proposition 65 List.

ANSI LABELING (Z129.1): **CAUTION! MAY CAUSE SKIN, EYE, AND RESPIRATORY TRACT IRRITATION.** Avoid contact with skin, eyes, and clothing. Avoid breathing vapors, mists, or sprays. Do not taste or swallow. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling. Wear appropriate eye, hand, and body protection. Avoid exposure to elevated temperatures. **FIRST-AID**: In case of contact, immediately flush skin or eyes with plenty of water for at least 20 minutes while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If swallowed, do not induce vomiting. Get medical attention. **IN CASE OF FIRE**: Use water fog, foam, dry chemical, or CO<sub>2</sub>. **IN CASE OF SPILL**: Absorb spill with polypads and place in suitable container. Place residual in appropriate container and seal. Dispose of in accordance with U.S. Federal, State, and local hazardous waste disposal regulations or those of Canada, EU Member States or Australia. Consult Material Safety Data Sheet for additional information.

#### **CANADIAN REGULATIONS:**

CANADIAN DSL/NDL INVENTORY STATUS: It cannot be confirmed that the proprietary components of this product are on the DSL Inventory.

OTHER CANADIAN REGULATIONS: Not applicable.

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS: It cannot be confirmed that the proprietary components of this product are not on the CEPA Priorities Substances Lists.

CANADIAN WHMIS CLASSIFICATION and SYMBOLS: Not applicable.

#### **EUROPEAN UNION INFORMATION:**

LABELING AND CLASSIFICATION: This product does meet the definition of Irritant as defined by European Union Council Directive 67/548/EEC and subsequent Directive.

Classification: Irritant.

Risk Phrases: [R 43] May cause sensitization by skin contact. [R 52/53] Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## 15. REGULATORY INFORMATION (Continued)

### EUROPEAN UNION INFORMATION (continued):

#### LABELING AND CLASSIFICATION (continued):

Safety Phrases: [S 24] Avoid contact with skin. [S 36/37] Wear suitable protective clothing and gloves. [S 60] This material and its container must be disposed of as hazardous waste. [S 61] Avoid release to the environment. Refer to special instructions/Safety data sheets.  
Annex II Hazard Symbol: Xi



### AUSTRALIAN INFORMATION:

AUSTRALIAN INVENTORY OF CHEMICAL SUBSTANCES (AICS) STATUS: It cannot be confirmed that the proprietary components of this product are listed on the AICS.

HAZARDOUS SUBSTANCES INFORMATION SYSTEM (HSIS): It cannot be confirmed that the proprietary components of this product are not listed in the HSIS.

CLASSIFICATION: This product does meet the definition of Irritant as defined by the Australian National Occupational Health and Safety Commission [NOHSC(1008:2004)].

Classification: Irritant.

Risk Phrases: [R 43] May cause sensitization by skin contact. [R 52/53] Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Phrases: [S 24] Avoid contact with skin. [S 36/37] Wear suitable protective clothing and gloves. [S 60] This material and its container must be disposed of as hazardous waste. [S 61] Avoid release to the environment. Refer to special instructions/Safety data sheets.

Hazard Symbol: Xi



POISONS SCHEDULE NUMBER: Not applicable.

### NEW ZEALAND INFORMATION:

HAZARDOUS SUBSTANCES AND NEW ORGANISMS ACT (1996): It cannot be confirmed that the proprietary components of this product are not registered as hazardous substances with the Environmental Risk Management Authority.

### JAPANESE INFORMATION:

JAPANESE ENCS: It cannot be confirmed that the proprietary components of this product are on the ENCS Inventory.

JAPANESE MINISTRY OF ECONOMY, TRADE, AND INDUSTRY (METI) STATUS: It cannot be confirmed that the proprietary components of this product are not listed as Class I Specified Chemical Substances, Class II Specified

Chemical Substances, or Designated Chemical Substances by the Japanese METI.

POISONOUS AND DELETERIOUS SUBSTANCES CONTROL LAW: It cannot be confirmed that the proprietary components of this product are not listed as a Specified Poisonous Substance under the Poisonous and Deleterious Substances Control Law.

---

## 16. OTHER INFORMATION

### **PREPARED BY:**

CHEMICAL SAFETY ASSOCIATES, Inc.  
PO Box 1961, Hilo, HI 96721 • 800/441-3365 808/969-4846

### **DATE OF PRINTING:**

April 29, 2010

## DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these, which are commonly used, include the following:

**CAS #:** This is the Chemical Abstract Service Number that uniquely identifies each constituent.

### **EXPOSURE LIMITS IN AIR:**

**CEILING LEVEL:** The concentration that shall not be exceeded during any part of the working exposure.

**DFG MAKs:** Federal Republic of Germany Maximum Concentration Values in the workplace. Exposure limits are given as TWA (Time-Weighted Average) or PEAK (short-term exposure) values.

**DFG MAK Germ Cell Mutagen Categories:** **1:** Germ cell mutagens that have been shown to increase the mutant frequency in the progeny of exposed humans. **2:** Germ cell mutagens that have been shown to increase the mutant frequency in the progeny of exposed mammals. **3A:** Substances that have been shown to induce genetic damage in germ cells of human of animals, or which produce mutagenic effects in somatic cells of mammals *in vivo* and have been shown to reach the germ cells in an active form. **3B:** Substances that are suspected of being germ cell mutagens because of their genotoxic effects in mammalian somatic cell *in vivo*; in exceptional cases, substances for which there are no *in vivo* data, but that are clearly mutagenic *in vitro* and structurally related to known *in vivo* mutagens. **4:** Not applicable (Category 4 carcinogenic substances are those with non-genotoxic mechanisms of action. By definition, germ cell mutagens are genotoxic. Therefore, a Category 4 for germ cell mutagens cannot apply. At some time in the future, it is conceivable that a Category 4 could be established for genotoxic substances with primary targets other than DNA [e.g. purely aneugenic substances] if research results make this seem sensible.) **5:** Germ cell mutagens, the potency of which is considered to be so low that, provided the MAK value is observed, their contribution to genetic risk for humans is expected not to be significant.

### **EXPOSURE LIMITS IN AIR (continued):**

**DFG MAK Pregnancy Risk Group Classification:** **Group A:** A risk of damage to the developing embryo or fetus has been unequivocally demonstrated. Exposure of pregnant women can lead to damage of the developing organism, even when MAK and BAT (Biological Tolerance Value for Working Materials) values are observed.

**Group B:** Currently available information indicates a risk of damage to the developing embryo or fetus must be considered to be probable. Damage to the developing organism cannot be excluded when pregnant women are exposed, even when MAK and BAT values are observed. **Group C:** There is no reason to fear a risk of damage to the developing embryo or fetus when MAK and BAT values are observed. **Group D:** Classification in one of the groups A-C is not yet possible because, although the data available may indicate a trend, they are not sufficient for final evaluation.

**IDLH:** Immediately Dangerous to Life and Health. This level represents a concentration from which one can escape within 30-minutes without suffering escape-preventing or permanent injury.

**LOQ:** Limit of Quantitation.

**NE:** Not Established. When no exposure guidelines are established, an entry of NE is made for reference.

**NIC:** Notice of Intended Change.

**NIOSH CEILING:** The exposure that shall not be exceeded during any part of the workday. If instantaneous monitoring is not feasible, the ceiling shall be assumed as a 15-minute TWA exposure (unless otherwise specified) that shall not be exceeded at any time during a workday.

**NIOSH RELs:** NIOSH's Recommended Exposure Limits.

# DEFINITION OF TERMS (Continued)

## EXPOSURE LIMITS IN AIR (continued):

**PEL:** OSHA's Permissible Exposure Limits. This exposure value means exactly the same as a TLV, except that it is enforceable by OSHA. The OSHA Permissible Exposure Limits are based in the 1989 PELs and the June, 1993 Air Contaminants Rule (Federal Register: 58: 35338-35351 and 58: 40191). Both the current PELs and the vacated PELs are indicated. The phrase, "Vacated 1989 PEL" is placed next to the PEL that was vacated by Court Order.

**SKIN:** Used when there is a danger of cutaneous absorption.

**STEL:** Short Term Exposure Limit, usually a 15-minute time-weighted average (TWA) exposure that should not be exceeded at any time during a workday, even if the 8-hr TWA is within the TLV-TWA, PEL-TWA or REL-TWA.

**TLV:** Threshold Limit Value. An airborne concentration of a substance that represents conditions under which it is generally believed that nearly all workers may be repeatedly exposed without adverse effect. The duration must be considered, including the 8-hour.

**TWA:** Time Weighted Average exposure concentration for a conventional 8-hr (TLV, PEL) or up to a 10-hr (REL) workday and a 40-hr workweek.

**WEEL:** Workplace Environmental Exposure Limits from the AIHA.

## HAZARDOUS MATERIALS IDENTIFICATION SYSTEM HAZARD RATINGS:

This rating system was developed by the National Paint and Coating Association and has been adopted by industry to identify the degree of chemical hazards.

**HEALTH HAZARD: 0 Minimal Hazard:** No significant health risk, irritation of skin or eyes not anticipated. **Skin Irritation:** Essentially non-irritating. Mechanical irritation may occur. PII or Draize = 0. **Eye Irritation:** Essentially non-irritating, minimal effects

Toxicity 4-hrs  $LC_{50}$  Rat  $>$  20 mg/L. **1 Slight Hazard:** Minor reversible injury may occur; may irritate the stomach if swallowed; may defat the skin and exacerbate existing dermatitis. **Skin Irritation:** Slightly or mildly irritating. PII or Draize  $>$  0 < 5. **Eye Irritation:** Slightly or mildly irritating. PII or Draize  $>$  0 < 5.

2000 mg/kg. **Inhalation Toxicity  $LC_{50}$  4-hrs Rat  $>$  2-20 mg/L. **2 Moderate Hazard:** Temporary or transitory injury may occur; prolonged exposure may affect the CNS. **Skin Irritation:** Moderately irritating; primary irritant; sensitizer. PII or Draize  $\geq$  5, with no destruction of dermal tissue. **Eye Irritation:** Moderately to severely irritating;**

Draize = 26-100, with reversible effects. **Oral Toxicity  $LD_{50}$  Rat  $>$  50-500 mg/kg.**

**3 Serious Hazard:** Major injury likely unless prompt action is taken and medical treatment is given; high level of toxicity; corrosive. **Skin Irritation:** Severely irritating and/or corrosive; may cause destruction of dermal tissue, skin burns, and dermal necrosis. PII or Draize  $>$  5-8, with destruction of tissue. **Eye Irritation:** Corrosive, irreversible destruction of ocular tissue; corneal involvement or irritation persisting for more than 21 days. Draize  $>$  80 with effects irreversible in 21

200 mg/kg. **Inhalation Toxicity  $LC_{50}$  4-hrs Rat  $>$  0.05-0.5 mg/L. **4 Severe Hazard:** Life-threatening; major or permanent damage may result from single or repeated exposures; extremely toxic; irreversible injury may result from brief contact. **Skin Irritation:** Not appropriate. Do not rate as a 4, based on skin irritation alone. **Eye Irritation:** Not appropriate. Do not rate as a 4, based on skin irritation alone. **Eye Irritation:** Not appropriate. Do not rate as a 4, based on skin irritation alone. **Eye Irritation:** Not appropriate. Do not rate as a 4, based on skin irritation alone.**

Toxicity  $LD_{50}$  Rat  $\leq$  1 mg/kg. **Dermal Toxicity  $LD_{50}$  Rat or Rabbit:  $\leq$  20 mg/kg.** **Inhalation Toxicity  $LC_{50}$  4-hrs Rat  $\leq$  0.05 mg/L.**

**FLAMMABILITY HAZARD: 0 Minimal Hazard:** Materials that will not burn in air when exposed to a temperature of 815.5°C (1500°F) for a period of 5 minutes. **1 Slight Hazard:** Materials that must be pre-heated before ignition can occur. Material requires considerable pre-heating, under all ambient temperature conditions before ignition and combustion can occur. This usually includes the following: Materials that will burn in air when exposed to a temperature of 815.5°C (1500°F) for a period of 5 minutes or less; Liquids, solids and semisolids having a flash point at or above 93.3°C (200°F) (i.e. OSHA Class IIIB); and Most ordinary combustible materials (e.g. wood, paper, etc.). **2 Moderate Hazard:** Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. Materials in this degree would not, under normal conditions, form hazardous atmospheres in air, but under high ambient temperatures or moderate heating may release vapor in sufficient quantities to produce hazardous atmospheres with air. This usually includes the following: Liquids having a flash-point at or above 37.8°C (100°F); Solid materials in the form of course dusts that may burn rapidly but that generally do not form explosive atmospheres; Solid materials in a fibrous or shredded form that may burn rapidly and create flash fire hazards (e.g. cotton, sisal, hemp); and Solids and semisolids (e.g. viscous and slow flowing as asphalt) that readily give off flammable vapors. **3 Serious Hazard:** Liquids and solids that can be ignited under almost all ambient temperature conditions. Materials in this degree produce hazardous atmospheres with air under almost all ambient temperatures, or, unaffected by ambient temperature, are readily ignited under almost all conditions. This usually includes the following: Liquids having a flash point below 22.8°C (73°F) and having a boiling point at or above 38°C (100°F) and below 22.8°C (73°F) and below 37.8°C (100°F) (i.e. OSHA Class IB and IC); Materials that on account of their physical form or environmental conditions can form explosive mixtures with air and are readily dispersed in air (e.g., dusts of combustible solids, mists or droplets of flammable liquids); and Materials that burn extremely rapidly, usually by reason of self-contained oxygen (e.g. dry nitrocellulose and many organic peroxides). **4 Severe Hazard:** Materials that will rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air, and that will burn readily. This usually includes the following: Flammable gases; Flammable cryogenic materials; Any liquid or gaseous material that is liquid while under pressure and has a flash point below 22.8°C (73°F) and a boiling point below 37.8°C (100°F) (i.e. OSHA Class IA); and Materials that ignite spontaneously when exposed to air at a temperature of 54.4°C (130°F) or below (pyrophoric).

## HAZARDOUS MATERIALS IDENTIFICATION SYSTEM HAZARD RATINGS (continued):

**PHYSICAL HAZARD: 0 Water Reactivity:** Materials that do not react with water. **Organic Peroxides:** Materials that are normally stable, even under fire conditions and will not react with water. **Explosives:** Substances that are Non-Explosive. **Compressed Gases:** No Rating. **Pyrophorics:** No Rating. **Oxidizers:** No 0 rating. **Unstable Reactives:** Substances that will not polymerize, decompose, condense, or self-react. **1 Water Reactivity:** Materials that change or decompose upon exposure to moisture. **Organic Peroxides:** Materials that are normally stable, but can become unstable at high temperatures and pressures. These materials may react with water, but will not release energy violently. **Explosives:** Division 1.5 & 1.6 explosives. Substances that are very insensitive explosives or that do not have a mass explosion hazard. **Compressed Gases:** Pressure below OSHA definition. **Pyrophorics:** No Rating. **Oxidizers:** Packaging Group III oxidizers; Solids: any material that in either concentration tested, exhibits a mean burning time less than or equal to the mean burning time of a 3:7 potassium bromate/cellulose mixture and the criteria for Packing Group I and II are not met. Liquids: any material that exhibits a mean pressure rise time less than or equal to the pressure rise time of a 1:1 nitric acid (65%)/cellulose mixture and the criteria for Packing Group I and II are not met. **Unstable Reactives:** Substances that may decompose, condense, or self-react, but only under conditions of high temperature and/or pressure and have little or no potential to cause significant heat generation or explosion hazard. Substances that readily undergo hazardous polymerization in the absence of inhibitors. **2 Water Reactivity:** Materials that may react violently with water. **Organic Peroxides:** Materials that, in themselves, are normally unstable and will readily undergo violent chemical change, but will not detonate. These materials may also react violently with water. **Explosives:** Division 1.4 explosives. Explosive substances where the explosive effects are largely confined to the package and no projection of fragments of appreciable size or range are expected. An external fire must not cause virtually instantaneous explosion of almost the entire contents of the package. **Compressed Gases:** Pressurized and meet OSHA definition but  $<$  514.7 psi absolute at 21.1°C (70°F) [500 psig]. **Pyrophorics:** No Rating. **Oxidizers:** Packaging Group II oxidizers. Solids: any material that, either in concentration tested, exhibits a mean burning time of less than or equal to the mean burning time of a 2:3 potassium bromate/cellulose mixture and the criteria for Packing Group I are not met. Liquids: any material that exhibits a mean pressure rise time less than or equal to the pressure rise of a 1:1 aqueous sodium chlorate solution (40%)/cellulose mixture and the criteria for Packing Group I are not met. **Reactives:** Substances that may polymerize, decompose, condense, or self-react at ambient temperature and/or pressure, but have a low potential (or low risk) for significant heat generation or explosion. Substances that readily form peroxides upon exposure to air or oxygen at room temperature. **3 Water Reactivity:** Materials that may form explosive reactions with water. **Organic Peroxides:** Materials that are capable of detonation or explosive reaction, but require a strong initiating source or must be heated under confinement before initiation; or materials that react explosively with water. **Explosives:** Division 1.3 explosives. Explosive substances that have a fire hazard and either a minor blast hazard or a minor projection hazard or both, but do not have a mass explosion hazard. **Compressed Gases:** Pressure  $\geq$  514.7 psi absolute at 21.1°C (70°F) [500 psig]. **Pyrophorics:** No Rating. **Oxidizers:** Packaging Group I oxidizers. Solids: any material that, in either concentration tested, exhibits a mean burning time less than the mean burning time of a 3:2 potassium bromate/cellulose mixture. Liquids: any material that spontaneously ignites when mixed with cellulose in a 1:1 ratio, or which exhibits a mean pressure rise time less than the pressure rise time of a 1:1 perchloric acid (50%)/cellulose mixture. **Unstable Reactives:** Substances that may polymerize, decompose, condense, or self-react at ambient temperature and/or pressure and have a moderate potential (or moderate risk) to cause significant heat generation or explosion. **4 Water Reactivity:** Materials that react explosively with water without requiring heat or confinement. **Organic Peroxides:** Materials that are readily capable of detonation or explosive decomposition at normal temperature and pressures. **Explosives:** Division 1.1 & 1.2 explosives. Explosive substances that have a mass explosion hazard or have a projection hazard. A mass explosion is one that affects almost the entire load instantaneously. **Compressed Gases:** No Rating. **Pyrophorics:** Add to the definition of Flammability 4. **Oxidizers:** No 4 rating. **Unstable Reactives:** Substances that may polymerize, decompose, condense, or self-react at ambient temperature and/or pressure and have a high potential (or high risk) to cause significant heat generation or explosion.

## NATIONAL FIRE PROTECTION ASSOCIATION HAZARD RATINGS:

**HEALTH HAZARD: 0** Materials that, under emergency conditions, would offer no

acute inhalation toxicity greater than 2000 mg/L. Materials with an LD<sub>50</sub> for acute oral toxicity greater than 2000 mg/kg. Materials essentially non-irritating to the respiratory tract, eyes, and skin.

5,000 ppm but less than or equal to 10,000 ppm. Dusts and mists with a GNL<sub>10</sub> for acute inhalation toxicity greater than 10 mg/L but less than or equal to 200 mg/L.

Materials with an LD<sub>50</sub> for acute dermal toxicity greater than 1000 mg/kg but less than or equal to 2000 mg/kg. Materials that slightly to moderately irritate the respiratory tract, eyes and skin. Materials with an LD<sub>50</sub> for acute oral toxicity greater than 500 mg/kg but less than or equal to 2000 mg/kg.

**2** Materials that, under emergency conditions, can cause temporary incapacitation or residual injury. Gases with an LC<sub>50</sub> for acute inhalation toxicity greater than 3,000 ppm but less than or equal to 5,000

greater than one-fifth its LC<sub>50</sub> for acute inhalation toxicity, if its LC<sub>50</sub> is less than or equal to 5000 ppm and that does not meet the criteria for either degree of hazard 3 or degree of hazard 4. Dusts and mists with an LC<sub>50</sub> for acute inhalation toxicity greater than 2 mg/L but less than or equal to 10 mg/L. Materials with an LD<sub>50</sub> for acute dermal toxicity greater than 200 mg/kg but less than or equal to 1000 mg/kg.

# DEFINITION OF TERMS (Continued)

## NATIONAL FIRE PROTECTION ASSOCIATION HAZARD RATINGS (continued):

**2 (continued):** Compressed liquefied gases with boiling points between -30°C (-22°F) and -55°C (-66.5°F) that cause severe tissue damage, depending on duration of exposure. Materials that are respiratory irritants. Materials that cause severe, but

mg/kg but less than or equal to 500 mg/kg. for acute oral toxicity is greater than 50

condition to cause serious or permanent injury. Gases with an LC<sub>50</sub> for acute

1,000 ppm but less than or equal to 3,000 ppm. Any

liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater its

LC for acute inhalation toxicity, if its LC<sub>50</sub> is less than or equal to 3000 ppm and that

does not meet the criteria for degree of hazard 4. Dusts and mists with an LC<sub>50</sub> for

acute inhalation toxicity greater than 0.5 mg/L but less than or equal to 2 mg/L.

Materials with an LD<sub>50</sub> for acute dermal toxicity greater than 40 mg/kg but less than or

equal to 200 mg/kg. <sup>50</sup> Materials that are corrosive to the respiratory tract. Materials that

are corrosive to the eyes or cause irreversible corneal opacity. Materials corrosive to

the skin. Cryogenic gases that cause frostbite and irreversible tissue damage.

Compressed liquefied gases with boiling points below -55°C (-66.5°F) that cause

frostbite and irreversible tissue damage. Materials with an LD<sub>50</sub> for acute oral toxicity

greater than 5 mg/kg but less than or equal to 50 mg/kg. <sup>fo4</sup> Materials that, under

emergency conditions, can be lethal. Gases with an LC<sub>50</sub> <sup>ess</sup> less than or equal to 1,000 ppm. Any liquid whose saturated vapor concentration at

20°C (68°F) is equal to or greater than ten times its LC for acute inhalation toxicity, if

its LC<sub>50</sub> is less than or equal to 1000 ppm. Dusts and mists whose LC<sub>50</sub> for acute

inhalation toxicity is less than or equal to 0.5 mg/L. Materials whose LD<sub>50</sub> for acute

dermal toxicity is less than or equal to 40 mg/kg. Materials whose LD<sub>50</sub> for acute oral

toxicity is less than or equal to 5 mg/kg. <sup>50</sup>

**FLAMMABILITY HAZARD: 0** Materials that will not burn under typical fire conditions,

including intrinsically noncombustible materials such as concrete, stone, and sand.

Materials that will not burn in air when exposed to a temperature of 816°C (1500°F) for

a period of 5 minutes in according with Annex D of NFPA 704. **1** Materials that must

be preheated before ignition can occur. Materials in this degree require considerable

preheating, under all ambient temperature conditions, before ignition and combustion

can occur: Materials that will burn in air when exposed to a temperature of 816°C

(1500°F) for a period of 5 minutes in according with Annex D of NFPA 704. Liquids,

solids, and semisolids having a flash point at or above 93.4°C (200°F) (i.e. Class IIIB

liquids). Liquids with a flash point greater than 35°C (95°F) that do not sustain

combustion when tested using the *Method of Testing for Sustained Combustibility*, per

49 CFR 173, Appendix H or the UN *Recommendations on the Transport of Dangerous*

*Goods, Model Regulations* (current edition) and the related *Manual of Tests and*

*Criteria* (current edition). Liquids with a flash point greater than 35°C (95°F) in a water-

miscible solution or dispersion with a water non-combustible liquid/solid content of

more than 85% by weight. Liquids that have no fire point when tested by ASTM D 92,

*Standard Test Method for Flash and Fire Points by Cleveland Open Cup*, up to the

boiling point of the liquid or up to a temperature at which the sample being tested

shows an obvious physical change. Combustible pellets with a representative

diameter of greater than 2 mm (10 mesh). Most ordinary combustible materials.

Solids containing greater than 0.5% by weight of a flammable or combustible solvent

are rated by the closed cup flash point of the solvent. **2** Materials that must be

moderately heated or exposed to relatively high ambient temperatures before ignition

can occur. Materials in this degree would not under normal conditions form hazardous

atmospheres with air, but under high ambient temperatures or under moderate

heating could release vapor in sufficient quantities to produce hazardous atmospheres

with air. Liquids having a flash point at or above 37.8°C (100°F) and below 93.4°C

(200°F) (i.e. Class II and Class IIIA liquids.) Solid materials in the form of powders or

coarse dusts of representative diameter between 420 microns (40 mesh) and 2 mm

(10 mesh) that burn rapidly but that generally do not form explosive mixtures with air.

Solid materials in fibrous or shredded form that burn rapidly and create flash fire

hazards, such as cotton, sisal, and hemp. Solids and semisolids that readily give off

flammable vapors. Solids containing greater than 0.5% by weight of a flammable or

combustible solvent are rated by the closed cup flash point of the solvent. **3** Liquids

and solids that can be ignited under almost all ambient temperature conditions.

Materials in this degree produce hazardous atmospheres with air under almost all

ambient temperatures or, though unaffected by ambient temperatures, are readily

ignited under almost all conditions. Liquids having a flash point below 22.8°C (73°F)

and having a boiling point at or above 37.8°C (100°F) and those liquids having a flash

point at or above 22.8°C (73°F) and below 37.8°C (100°F) (i.e. Class IB and IC

liquids). Materials that on account of their physical form or environmental conditions

can form explosive mixtures with air and are readily dispersed in air. Flammable or

combustible dusts with representative diameter less than 420 microns (40 mesh).

Materials that burn with extreme rapidity, usually by reason of self-contained oxygen

(e.g. dry nitrocellulose and many organic peroxides). Solids containing greater than

0.5% by weight of a flammable or combustible solvent are rated by the closed cup

flash point of the solvent. **4** Materials that will rapidly or completely vaporize at

atmospheric pressure and normal ambient temperature or that are readily dispersed in

air and will burn readily. Flammable gases. Flammable cryogenic materials. Any liquid

or gaseous materials that is liquid while under pressure and has a flash point below

22.8°C (73°F) and a boiling point below 37.8°C (100°F) (i.e. Class IA liquids).

Materials that ignite when exposed to air, Solids containing greater than 0.5% by

weight of a flammable or combustible solvent are rated by the closed cup flash point of

the solvent.

**INSTABILITY HAZARD: 0** Materials that in themselves are normally stable, even under fire conditions. Materials that have an instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) below 0.01 W/mL. Materials that do not exhibit an exotherm at temperatures less than or equal to 500°C (932°F) when tested by differential scanning calorimetry.

## NATIONAL FIRE PROTECTION ASSOCIATION HAZARD RATINGS (continued):

**INSTABILITY HAZARD (continued): 1** Materials that in themselves are normally stable, but that can become unstable at elevated temperatures and pressures. Materials that have an instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 0.01 W/mL and below 10 W/mL. **2**

Materials that readily undergo violent chemical change at elevated temperatures and pressures. Materials that have an instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 10 W/mL and below 100W/mL. **3** Materials that in themselves are capable of detonation or explosive decomposition or explosive reaction, but that require a strong initiating source or that must be heated under confinement before initiation. Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 100 W/mL and below 1000 W/mL. Materials that are sensitive to thermal or mechanical shock at elevated temperatures and pressures. **4** Materials that in themselves are readily capable of detonation or explosive decomposition or explosive reaction at normal temperatures and pressures. Materials that are sensitive to localized thermal or mechanical shock at normal temperatures and pressures.

Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) of 1000 W/mL or greater.

**FLAMMABILITY LIMITS IN AIR:**

Much of the information related to fire and explosion is derived from the National Fire Protection Association (**NFPA**). **Flash Point:** Minimum temperature at which a liquid gives off sufficient vapor to form an ignitable mixture with air near the surface of the liquid or within the test vessel used. **Autoignition Temperature:** Minimum temperature of a solid, liquid, or gas required to initiate or cause self-sustained combustion in air with no other source of ignition. **LEL:** Lowest concentration of a flammable vapor or gas/air mixture that will ignite and burn with a flame. **UEL:** Highest concentration of a flammable vapor or gas/air mixture that will ignite and burn with a flame.

**TOXICOLOGICAL INFORMATION:**

**Human and Animal Toxicology:** Possible health hazards as derived from human

LCs:enLethal<sub>50</sub>Concentrations(gases)srthatikills) 50%ikofswthe%exposedexanimals.nimals

Concentration expressed in parts of material per million parts of air or water. **ppm:**

Concentration expressed in weight of substance per volume of air. **mg/kg:** Quantity of

material, by weight, administered to a test subject, based on their body weight in kg.

**TDLo:** Lowest dose to cause a symptom. **ICLo:** Lowest concentration to cause a

symptom. **TD<sub>0</sub>**, **LDLo**, and **LD<sub>0</sub>**, or **TC**, **TC<sub>0</sub>**, **LCLo**, and **LC<sub>0</sub>**: Lowest dose (or

concentration) to cause lethal or toxic effects.

**Cancer Information:** **IARC:** International Agency for Research on Cancer. **NTP:**

National Toxicology Program. **RTECS:** Registry of Toxic Effects of Chemical

Substances. IARC and NTP rate chemicals on a scale of decreasing potential to

cause human cancer with rankings from 1 to 4. Subrankings (2A, 2B, etc.) are also

used. **Other Information:** **BEI:** ACGIH Biological Exposure Indices, represent the

levels of determinants which are most likely to be observed in specimens collected

from a healthy worker who has been exposed to chemicals to the same extent as a

worker with inhalation exposure to the TLV.

**ECOLOGICAL INFORMATION:**

**EC:** Effect concentration in water. **BCF:** Bioconcentration Factor, which is used to

Oil/Water Distribution is used to assess a substance's behavior in the environment. Coefficient of

**REGULATORY INFORMATION:**

**U.S.:**

**EPA:** U.S. Environmental Protection Agency. **ACGIH:** American Conference of

Governmental Industrial Hygienists, a professional association that establishes

exposure limits. **OSHA:** U.S. Occupational Safety and Health Administration. **NIOSH:**

National Institute of Occupational Safety and Health, which is the research arm of

OSHA. **DOT:** U.S. Department of Transportation. **TC:** Transport Canada. **SARA:**

Superfund Amendments and Reauthorization Act. **TSCA:** U.S. Toxic Substance

Control Act. **CERCLA:** Comprehensive Environmental Response, Compensation, and

Liability Act. Marine Pollutant status according to the DOT; CERCLA or Superfund;

and various state regulations. This section also includes information on the

precautionary warnings that appear on the material's package label.

**CANADA:**

**WHMIS:** Canadian Workplace Hazardous Materials Information System. **TC:**

Transport Canada. **DSL/NDSL:** Canadian Domestic/Non-Domestic Substances List.

**EUROPE:**

**EU:** European Union (formerly known as the EEC, European Economic Community).

**EINECS:** European Inventory of Non-Existing Chemical Substances. **ARD:** European

Agreement Concerning the International Carriage of Dangerous Goods by Road. **RID:**

International Regulations Concerning the Carriage of Dangerous Goods by Rail.

**AUSTRALIA:**

**AICS:** Australian Inventory of Chemical Substances. **NOHSC:** National Occupational

Health & Safety Code.

**JAPAN:**

**METI:** Ministry of Economy, Trade and Industry.