

## SAFETY DATA SHEET

This Safety Data Sheet conforms to ANSI Z400.5, and to the format requirements and the International Chemical Safety Cards of the Global Harmonizing System.


THIS SDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD)

IMPORTANT: Read this SDS before handling & disposing of this product.

Pass this information on to employees, customers, & users of this product.

### SECTION 1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

PRODUCT IDENTITY: ALL SOLV EXTREME CS01  
PRODUCT PURPOSE: SPOTTER  
COMPANY IDENTITY: Bridgepoint Systems  
COMPANY ADDRESS: 4282 S 590 W  
COMPANY CITY: Salt Lake City, UT 84123  
COMPANY PHONE: 1-800-658-5314  
EMERGENCY PHONES: INFOTRAC: 1-800-535-5053 (USA)



### SECTION 2. HAZARDS IDENTIFICATION

**DANGER!!**

EXPOSURE PREVENTION: STRICT HYGIENE!

#### HAZARD STATEMENTS:

H100s = General, H200s = Physical, H300s = Health, H400s = Environmental

H224 Extremely flammable liquid and vapor.  
H315 Causes skin irritation.  
H320 Causes eye irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.

#### PRECAUTIONARY STATEMENTS:

P100s = General, P200s = Prevention, P300s = Response, P400s = Storage, P500s = Disposal

P210 Keep away from heat/sparks/open flames/hot surfaces - No smoking.  
P262 Do not get in eyes, on skin, or on clothing.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present & easy to do - Continue rinsing.  
P403 Store in a well-ventilated place.  
P404 Store in a closed container.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

MATERIAL	CAS#	EINECS#	WT %
2(2-Butoxyethoxy)ethanol	112-34-5	203-961-6	Trade Secret
Acetone	67-64-1	200-662-2	Trade Secret
Isopropanol	67-63-0	200-661-7	Trade Secret

Trace components: Trace ingredients (if any) are present in < 1% concentration, (< 0.1% for potential carcinogens, reproductive toxins, respiratory tract mutagens, and sensitizers). None of the trace ingredients contribute significant additional hazards at the concentrations that may be present in this product. All pertinent hazard information has been provided in this document, per the requirements of the Federal Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalents, and Canadian Hazardous Materials Identification System Standard (CPR 4).

SEE SECTIONS 8, 11 & 12 FOR TOXICOLOGICAL INFORMATION.

### SECTION 4. FIRST AID MEASURES

#### GENERAL ADVICE:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists, refer to Section 8 for specific personal protective equipment.

#### EYE CONTACT:

If this product enters the eyes, open eyes while under gently running water. Use sufficient force to open eyelids. "Roll" eyes to expose more surface. Minimum flushing is for 15 minutes. Seek immediate medical attention.

COMPANY IDENTITY: Bridgepoint Systems  
PRODUCT IDENTITY: ALL SOLV EXTREME

SDS DATE: 05/07/2013  
ORIGINAL: 05/07/2013

**SECTION 4. FIRST AID MEASURES (CONTINUED)**

**SKIN CONTACT:**

If the product contaminates the skin, immediately begin decontamination with running water. Minimum flushing is for 15 minutes. Remove contaminated clothing, taking care not to contaminate eyes. If skin becomes irritated and irritation persists, medical attention may be necessary. Wash contaminated clothing before reuse, discard contaminated shoes.

**INHALATION:**

After high vapor exposure, remove to fresh air. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. Keep person warm and at rest. breathing is difficult, give oxygen. If breathing has stopped, trained personnel should immediately begin artificial respiration. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. If the heart has stopped, trained personnel should immediately begin cardiopulmonary resuscitation (CPR). Seek immediate medical attention. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

**SWALLOWING:**

If swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. If professional advice is not available, give two glasses of water to drink. DO NOT INDUCE VOMITING. Never induce vomiting or give liquids to someone who is unconscious, having convulsions, or unable to swallow. Seek immediate medical attention.

**NOTES TO PHYSICIAN:**

There is no specific antidote. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. Any material aspirated during vomiting may cause lung injury. Therefore, emesis should not be induced mechanically or pharmacologically. If it is considered necessary to evacuate the stomach contents, this should be done by means least likely to cause aspiration (such as: Gastric lavage after endotracheal intubation).

**SECTION 5. FIRE FIGHTING MEASURES**

**FIRE & EXPLOSION PREVENTIVE MEASURES**

NO open flames, NO sparks, & NO smoking. Above flash point, use a closed system, ventilation, explosion-proof electrical equipment, lighting. Do NOT use compressed air for filling, discharging, or handling.

**EXTINGUISHING MEDIA**

Use dry powder, alcohol-resistant foam, water spray, water in large amounts, carbon dioxide.

**SPECIAL FIRE FIGHTING PROCEDURES**

Water spray may be ineffective on fire but can protect fire-fighters & cool closed containers. Use fog nozzles if water is used. Do not enter confined fire-space without full bunker gear. (Helmet with face shield, bunker coats, gloves & rubber boots). Use NIOSH approved positive-pressure self-contained breathing apparatus.

**UNUSUAL EXPLOSION AND FIRE PROCEDURES**

**EXTREMELY FLAMMABLE!! VAPORS CAN CAUSE FLASH FIRE**  
Isolate from oxidizers, heat, sparks, electric equipment & open flame. Closed containers may explode if exposed to extreme heat. Applying to hot surfaces requires special precautions. Empty container very hazardous! Continue all label precautions!

COMPANY IDENTITY: Bridgepoint Systems  
PRODUCT IDENTITY: ALL SOLV EXTREME

SDS DATE: 05/07/2013  
ORIGINAL: 05/07/2013

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

### **SPILL AND LEAK RESPONSE AND ENVIRONMENTAL PRECAUTIONS:**

Uncontrolled releases should be responded to by trained personnel using pre-planned procedures. Proper protective equipment should be used. In case of a spill, clear the affected area, protect people, and respond with trained personnel.

### **PERSONAL PROTECTIVE EQUIPMENT**

The proper personal protective equipment for incidental releases (such as: 1 Liter of the product released in a well-ventilated area), use impermeable gloves (triple-gloves (rubber gloves and nitrile gloves, over latex gloves), goggles, face shield, and appropriate body protection. In the event of a large release, use impermeable gloves, specific for the material handled, chemically resistant suit and boots, and hard hat. Self-Contained Breathing Apparatus or respirator may be required where engineering controls are not adequate or conditions for potential exposure exist. When respirators are required, select NIOSH/MSHA approved based on actual or potential airborne concentrations in accordance with latest OSHA and/or ANSI recommendations.

### **ENVIRONMENTAL PRECAUTIONS:**

Stop spill at source. Construct temporary dikes of dirt, sand, or any appropriate readily available material to prevent spreading of the material. Close or cap valves and/or block or plug hole in leaking container and transfer to another container. Keep from entering storm sewers and ditches which lead to waterways, and if necessary, call the local fire or police department for immediate emergency assistance.

### **CONTAINMENT AND CLEAN-UP MEASURES:**

Absorb spilled liquid with polypads or other suitable absorbent materials. If necessary, neutralize using suitable buffering material, (acid with soda ash or base with phosphoric acid), and test area with litmus paper to confirm neutralization. Clean up with non-combustible absorbent (such as: sand, soil, and so on). Shovel up and place all spill residue in suitable containers. dispose of at an appropriate waste disposal facility according to current applicable laws and regulations and product characteristics at time of disposal (see Section 13 - Disposal Considerations).

## **SECTION 7. HANDLING AND STORAGE**

### **HANDLING**

Isolate from oxidizers, heat, sparks, electric equipment & open flame.  
Use only with adequate ventilation. Avoid breathing of vapor or spray mist.  
Do not get in eyes, on skin or clothing. Wear OSHA Standard goggles or face shield.  
Consult Safety Equipment Supplier. Wear goggles, face shield, gloves, apron & footwear impervious to material. Wash clothing before reuse.  
Avoid free fall of liquid. Ground containers when transferring. Do not flame cut, saw, drill, braze, or weld. Empty container very hazardous! Continue all label precautions!

### **STORAGE**

Vapors may ignite explosively & spread long distances. Prevent vapor buildup. Put out pilot lights & turn off heaters, electric equipment & other ignition sources during use & until all vapors are gone. Keep in fireproof surroundings. Keep separated from strong oxidants. Keep cool. Keep dry. Use ventilation along the floor. Do not store above 49 C/120 F. Keep container tightly closed & upright when not in use to prevent leakage.

### **NONBULK: CONTAINERS:**

Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Material should be stored in secondary containers or in a diked area, as appropriate. Store containers away from incompatible chemicals (see Section 10, Stability and Reactivity). Post warning and "NO SMOKING" signs in storage and use areas, as appropriate. Empty containers should be handled with care. Never store food, feed, or drinking water in containers which held this product.

COMPANY IDENTITY: Bridgepoint Systems  
 PRODUCT IDENTITY: ALL SOLV EXTREME

SDS DATE: 05/07/2013  
 ORIGINAL: 05/07/2013

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

MATERIAL	CAS#	EINECS#	TWA (OSHA)	TLV (ACGIH)
2(2-Butoxyethoxy)ethanol	112-34-5	203-961-6	None Known	25 ppm
Acetone	67-64-1	200-662-2	1000 ppm	500 ppm A4
Isopropanol	67-63-0	200-661-7	400 ppm	200 ppm A4

MATERIAL	CAS#	EINECS#	CEILING	STEL (OSHA/ACGIH)	HAP
2(2-Butoxyethoxy)ethanol	112-34-5	203-961-6	None Known	None Known	Yes
Acetone	67-64-1	200-662-2	None Known	750 ppm	No
Isopropanol	67-63-0	200-661-7	None Known	400 ppm	No

Each component showing 'Yes' under "HAP" is an EPA Hazardous Air Pollutant.

### RESPIRATORY EXPOSURE CONTROLS

Seek professional advice prior to respirator selection and use.

Maintain airborne contaminant concentrations below exposure limits given above. If respiratory protection is needed, use only protection authorized in 29 CFR 1910.134, European Standard EN 149, or applicable State regulations. If adequate ventilation is not available or there is potential for airborne exposure above the exposure limits, a respirator may be worn up to the respirator exposure limitations, check with respirator equipment manufacturer's recommendations/limitations. For a higher level of protection, use positive pressure supplied air respiration protection or Self-Contained Breathing Apparatus or if oxygen levels are below 19.5% or are unknown.

### VENTILATION

LOCAL EXHAUST: Necessary                      MECHANICAL (GENERAL): Necessary  
 SPECIAL: None                                      OTHER: None  
 Please refer to ACGIH document, "Industrial Ventilation, A Manual of Recommended Practices", most recent edition, for details.

### EYE PROTECTION:

Splash goggles or safety glasses.

### HAND PROTECTION:

Wear appropriate impervious gloves for routine industrial use. Use impervious gloves for spill response, as stated in Section 6 of this SDS (Accidental Release Measures).

## SECTION 9. PHYSICAL & CHEMICAL PROPERTIES

APPEARANCE:	Cloudy Viscous Liquid
ODOR:	Ketone
ODOR THRESHOLD:	Not Available
pH (Neutrality):	Not Applicable
MELTING POINT/FREEZING POINT:	Not Available
BOILING RANGE (IBP,50%,Dry Point):	67 137 228* C / 153 280 444* F (*=End Point)
FLASH POINT (TEST METHOD):	<-6.7 C / <20 F (FCC)
BOILING POINT:	90 C / 194 F (CCS TM-011)
EVAPORATION RATE (n-BUTYL ACETATE=1):	Not Applicable
FLAMMABILITY CLASSIFICATION:	Class I B
LOWER FLAMMABLE LIMIT IN AIR (% by vol):	1.7
UPPER FLAMMABLE LIMIT IN AIR (% by vol):	Not Available
VAPOR PRESSURE (mm of Hg)@20 C	84.3
VAPOR DENSITY (air=1):	3.2
GRAVITY @ 68/68 F / 20/20 C:	
DENSITY:	0.942
SPECIFIC GRAVITY (Water=1):	0.943
POUNDS/GALLON:	7.856
WATER SOLUBILITY:	Appreciable
PARTITION COEFFICIENT (n-Octane/Water):	Not Available
AUTO IGNITION TEMPERATURE:	398 C / 750 F
DECOMPOSITION TEMPERATURE:	Not Available
REFRACTIVE INDEX:	1.404
VOCs (>0.044 Lbs/Sq In) :	Not Available
TOTAL VOC'S (TVOC)*:	3.0 Lbs/Gal

COMPANY IDENTITY: Bridgepoint Systems  
PRODUCT IDENTITY: ALL SOLV EXTREME

SDS DATE: 05/07/2013  
ORIGINAL: 05/07/2013

**SECTION 9. PHYSICAL & CHEMICAL PROPERTIES (CONTINUED)**

NONEXEMPT VOC'S (CVOC)\*: 0.2 Lbs/Gal  
HAZARDOUS AIR POLLUTANTS (HAPS): 26.2 Wt%  
NONEXEMPT VOC PARTIAL PRESSURE (mm of Hg @ 20 C) Not Available  
VISCOSITY @ 25 C (ASTM E2196): 1025 cPs  
\* Using California Air Resources Board (CARB) Rule 310.

**SECTION 10. STABILITY & REACTIVITY**

STABILITY

Stable under normal conditions.

CONDITIONS TO AVOID

Isolate from oxidizers, heat, sparks, electric equipment & open flame.

MATERIALS TO AVOID

Reacts with strong oxidants, causing fire & explosion hazard. Attacks

HAZARDOUS DECOMPOSITION PRODUCTS

Carbon Monoxide, Carbon Dioxide from burning.

HAZARDOUS POLYMERIZATION

Will not occur.

**SECTION 11. TOXICOLOGICAL INFORMATION**

**ACUTE HAZARDS**

EYE & SKIN CONTACT:

Primary irritation to skin, defatting, dermatitis.  
Absorption thru skin increases exposure.  
Primary irritation to eyes, redness, tearing, blurred vision.  
Liquid can cause eye irritation. Wash thoroughly after handling.

INHALATION:

Anesthetic. Irritates respiratory tract. Acute overexposure  
can cause serious nervous system depression. Vapor harmful.  
Breathing vapor can cause irritation.  
Acute overexposure can cause harm to kidneys, blood, nerves, liver, lungs.

SWALLOWING:

Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea.

**SUBCHRONIC HAZARDS/CONDITIONS AGGRAVATED**

CONDITIONS AGGRAVATED

Chronic overexposure can cause harm to kidneys, blood, nerves, liver, lungs.  
Persons with severe skin, liver or kidney problems should avoid use.

**CHRONIC HAZARDS**

CANCER, REPRODUCTIVE & OTHER CHRONIC HAZARDS:

This product has no carcinogens listed by IARC, NTP, NIOSH,  
OSHA or ACGIH, as of this date, greater or equal to 0.1%.  
Absorption thru skin may be harmful.

IRRITANCY OF PRODUCT: This product is irritating to contaminated tissue.

SENSITIZATION TO THE PRODUCT: No component of this product is known to be a sensitizer.

MUTAGENICITY: This product is not reported to produce mutagenic effects in humans.

EMBRYOTOXICITY: This product is not reported to produce embryotoxic effects in humans.

TERATOGENICITY: This product is not reported to produce teratogenic effects in humans.

COMPANY IDENTITY: Bridgepoint Systems  
 PRODUCT IDENTITY: ALL SOLV EXTREME

SDS DATE: 05/07/2013  
 ORIGINAL: 05/07/2013

### SECTION 11. TOXICOLOGICAL INFORMATION (CONTINUED)

REPRODUCTIVE TOXICITY: This product is not reported to cause reproductive effects in humans.

A mutagen is a chemical which causes permanent changes to genetic material (DNA) such that the changes will propagate through generational lines. An embryotoxin is a chemical which causes damage to a developing embryo (such as: within the eight weeks of pregnancy in humans), but the damage does not propagate across generational lines. A teratogen is a chemical which causes damage to a developing fetus, but the damage does not propagate across generational lines. A reproductive toxin is any substance which interferes in any way with the reproductive process.

#### MAMMALIAN TOXICITY INFORMATION

MATERIAL	CAS#	EINECS#	LOWEST KNOWN LETHAL DOSE DATA
Acetone	67-64-1	203-961-6	LOWEST KNOWN LD50 (ORAL) 5340.0 mg/kg (Rabbits)
Isopropanol	67-63-0	-	LOWEST KNOWN LC50 (VAPORS) 1600 ppm (Rats)
Diethylene Glycol Butyl Ether	112-34-5	200-662-2	LOWEST KNOWN LD50 (SKIN) 4120.0 mg/kg (Rabbits)

### SECTION 12. ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

#### EFFECT OF MATERIAL ON PLANTS AND ANIMALS:

This product may be harmful or fatal to plant and animal life if released into the environment. Refer to Section 11 (Toxicological Information) for further data on the effects of this product's components on test animals.

#### EFFECT OF MATERIAL ON AQUATIC LIFE:

The most sensitive known aquatic group to any component of this product is: Chub 1000 ppm or mg/L (24 hour exposure).  
 Keep out of sewers and natural water supplies.

#### MOBILITY IN SOIL

Mobility of this material has not been determined.

#### DEGRADABILITY

This product is completely biodegradable.

#### ACCUMULATION

Bioaccumulation of this product has not been determined.

### SECTION 13. DISPOSAL CONSIDERATIONS

Processing, use or contamination may change the waste disposal requirements. Do not dispose of on land, in surface waters, or in storm drains. Waste should be recycled or disposed of in accordance with regulations. Large amounts should be collected for reuse or consigned to licensed hazardous waste haulers for disposal.

**ALL DISPOSAL MUST BE IN ACCORDANCE WITH ALL FEDERAL, STATE, PROVINCIAL, AND LOCAL REGULATIONS. IF IN DOUBT, CONTACT PROPER AGENCIES. EPA CHARACTERISTIC: D001**

### SECTION 14. TRANSPORT INFORMATION

IF > 22928 LB / 10421 KG OF THIS PRODUCT IS IN 1 CONTAINER, IT EXCEEDS THE RQ OF ACETONE. "RQ" MUST BE PUT BEFORE THE DOT SHIPPING NAME.

DOT/TDG SHIP NAME: UN1993, Flammable Liquids, n.o.s.  
 (Contains: 2(2-Butoxyethoxy)ethanol, Acetone),  
 3, PG-II

49CFR Limited Qty: Inner packaging not over 1.0 L (0.3 gallons) net capacity

DRUM LABEL: (FLAMMABLE LIQUID)

IATA / ICAO: UN1993, Flammable Liquids, n.o.s.  
 (Contains: 2(2-Butoxyethoxy)ethanol, Acetone),

3, PG-II  
 COMPANY IDENTITY: Bridgepoint Systems  
 PRODUCT IDENTITY: ALL SOLV EXTREME

SDS DATE: 05/07/2013  
 ORIGINAL: 05/07/2013

#### SECTION 14. TRANSPORT INFORMATION (CONTINUED)

IMO / IMDG: UN1993, Flammable Liquids, n.o.s.  
 (Contains: 2(2-Butoxyethoxy)ethanol, Acetone),  
 3, PG-II  
 EMERGENCY RESPONSE GUIDEBOOK NUMBER: 128

#### SECTION 15. REGULATORY INFORMATION

EPA REGULATION:  
 SARA SECTION 311/312 HAZARDS: Acute Health, Fire



All components of this product are on the TSCA list.  
 SARA Title III Section 313 Supplier Notification  
 This product contains the indicated <\*> toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning & Community Right-To-Know Act of 1986 & of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material.

SARA TITLE III INGREDIENTS	CAS#	EINECS#	WT%	(REG. SECTION)	RQ(LBS)
*2(2-Butoxyethoxy)ethanol	112-34-5	203-961-6	20-30	(313)	None
Acetone	67-64-1	200-662-2	15-25	(311,312)	5000

Any release equal to or exceeding the RQ must be reported to the National Response Center (800-424-8802) and appropriate state and local regulatory agencies as described in 40 CFR 302.6 and 40 CFR 355.40 respectively. Failure to report may result in substantial civil and criminal penalties. State & local regulations may be more restrictive than federal regulations.

#### STATE REGULATIONS:

CALIFORNIA SAFE DRINKING WATER & TOXIC ENFORCEMENT ACT (PROPOSITION 65):  
 This product contains no chemicals known to the State of California to cause cancer or reproductive toxicity.

#### INTERNATIONAL REGULATIONS

The components of this product are listed on the chemical inventories of the following countries:  
 Australia (AICS), Canada (DSL or NDSL), China (IECSC), Europe (EINECS, ELINCS)G  
 Japan (METI/CSCS, MHLW/ISHL), South Korea (KECI), New Zealand (NZIoC),  
 Philippines (PICCS), Switzerland (SWISS), Taiwan (NECSI), USA (TSCA).

#### CANADA: WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS)

B2: Flammable Liquid.  
 D2B: Irritating to skin / eyes.

This product has been classified in accordance with hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

#### SECTION 16. OTHER INFORMATION

##### HAZARD RATINGS:

HEALTH (NFPA): 2, HEALTH (HMIS): 2, FLAMMABILITY: 4, PHYSICAL HAZARD: 0  
 (Personal Protection Rating to be supplied by user based on use conditions.)  
 This information is intended solely for the use of individuals trained in the NFPA & HMIS hazard rating systems.

##### EMPLOYEE TRAINING

See Section 2 for Risk & Safety Statements. Employees should be made aware of all hazards of this material (as stated in this SDS) before handling it.

SDS DATE: 05/07/2013

COMPANY IDENTITY: Bridgepoint Systems  
PRODUCT IDENTITY: ALL SOLV EXTREME

SDS DATE: 05/07/2013  
ORIGINAL: 05/07/2013

**SECTION 16. OTHER INFORMATION (CONTINUED)**

**NOTICE**

Bridgepoint Systems disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency.

Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon information contained herein.

This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.